

Product Datasheet

36-Port 10G Uplink Managed Industrial PoE Fiber Switch

ONV-IPS36368PFM



OVERVIEW

The ONV-IPS36368PFM is a 10G uplink managed industrial PoE fiber switch independently developed by ONV. It has 8*10/100/1000Base-T RJ45 ports and 24*100/1000M SFP fiber slot ports and 4*1/10G SFP+ fiber slot ports. Port 1-8 can support IEEE802.3af/at standard PoE power supply. single port PoE power reaches 30W, and the maximum PoE output power is 130W(at-250W). As a PoE power supply device, it can automatically detect and recognize power-compliant devices that meet the standard and supply power through the network cable. It can supply power to POE terminal equipment such as wireless AP, webcam, VoIP, industrial sensor through the network cable, and meet the network environment that needs high-density PoE power supply. It is suitable for intelligent transportation, rail transit, power industry, mining, petroleum, Industrial scenes such as shipping, metallurgy, and green energy construction form a cost-effective, stable and reliable communication network.

The ONV-IPS36368PFM has L2+ full network management function, supports IPV4/IPV6 management, supports static route full line rate forwarding, supports complete security protection mechanism, complete ACL/QoS policy and rich VLAN functions, and is easy to

manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as PoE power management, port traffic control, VLAN division, and SNMP through the Web network management mode.

FEATURE

■ Gigabit multi fiber port access, 10G uplink

- ◇ All series supports “Gigabit Ethernet port and Gigabit SFP port and 10G SFP+ uplink port” combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

■ Intelligent PoE power supply function

- ◇ 8*10/100/1000Base-T RJ45 ports, meeting the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.
- ◇ IEEE 802.3af/at PoE standard, without damaging non-PoE devices.
- ◇ Priority system for PoE port, it will supply power to the high priority level port first when the power budget is insufficient and avoid overwork of the device.
- ◇ PoE network management, realize PoE port power allocation, priority setting, port power status viewing, time scheduling, etc.

■ Security

- ◇ 802.1X authentication.

- ◊ Port isolation,Storm control.
- ◊ IP-MAC-VLAN-Port binding.

■ Strong business processing capability

- ◊ IEEE802.1Q VLAN, flexible VLAN division,Voice VLAN and QinQ configuration.
- ◊ QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including Equ, SP, WRR & SP+WRR.
- ◊ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.
- ◊ IGMP V1/V2 and IGMP Snooping.
- ◊ ERPS/STP/RSTP/MSTP.
- ◊ Static and dynamic aggregation.

■ Stable and reliable

- ◊ CCC,CE, FCC, RoHS.
- ◊ Low power consumption, galvanized steel casing, The fan active cooling.
- ◊ The user-friendly panel, it can show the device status through the LED indicator of PWR, Link, L/A,PoE.
- ◊ Self-developed power supply, high redundancy design, providing a long term and stable PoE power output.

■ Easy operation and maintenance management

- ◊ HTTPS, SSLV3, and SSHV1/V2.
- ◊ RMON, system log, LLDP, and port traffic statistics.
- ◊ CPU monitoring, memory monitoring, Ping test, and cable diagnose.
- ◊ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).

TECHNICAL SPECIFICATION

Model	ONV-IPS36368PFM	ONV-IPS36368PFM-at
Interface Characteristics		
Fixed Port		8*10/100/1000Base-T PoE ports (Data/Power) 24*100/1000Base-X uplink SFP fiber slot ports (Data) 4*1/10G uplink SFP+ fiber slot ports (Data) 1*Console RS232 port (115200,N,8,1)
Ethernet Port		Port 1-8 support 10/100/1000Base-T,auto-sensing,Full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission		10BASE-T: Cat3,4,5 UTP(\leq 100 meter) 100BASE-TX: Cat5 or later UTP(\leq 100 meter) 1000BASE-T: Cat5e or later UTP(\leq 100 meter)
Optical Fiber Port		Gigabit SFP /10G SFP+ optical fiber interface, default matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)
Optical Cable/ Distance		Multi mode: 850nm / 0 ~ 500M(1.25G), 850nm / 0 ~ 300M (10G); single mode: 1310nm / 0 ~ 40KM, 1550nm /0 ~ 120KM.
Chip Parameter		
Network Management Type	L2+	
Network Protocol		IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX , IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3ae 10GBase-LR/SR IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	598Gbps (non-blocking)	

Forwarding Rate@64byte	107.14Mpps	
MAC	32K	
Buffer Memory	32M	
Jumbo Frame	9.6K	
LED Indicator	Power: PWR (yellow), system:SYS (yellow); network:Link (yellow); PoE: PoE (green); Fiber port : L/A (green)	
Reset Switch	Yes, support one key to restore factory settings	
PoE & Power		
PoE Port	Port 1 to 8	
PoE Management	PoE working status Delay start of power supply PoE output priority configuration Scheduling of PoE operation and time Total power limit of PoE power supply PoE output power allocation, off& af &at	
Power Supply Pin	Default: 1/2 (+), 3/6 (-)	
Max Power Per Port	30W, IEEE802.3af/at	
Total PWR / Input Voltage	130W /(AC100-240V)	250W/ (AC100-240V)
Power Consumption	Standby<20W, Full Load<130W	Standby<25W, Full Load<250W
Power Input Interface	Dual input power interface design, AC power supply priority, support anti-reverse protection, power-off automatic switching DC connection; 2 sets of DC12-48V input interface; alarm switch interface; 1 set of AC power input interface	
Heat Dissipation	Low noise fan active cooling	
Power Supply	Built-in power supply, AC 100~240V 50-60Hz 2.3A	Built-in power supply, AC 100~240V 50-60Hz 4.1A

Physical Parameter

Operation TEMP / Humidity	-40~+80°C; 5%~90% RH Non condensing	
Storage TEMP / Humidity	-40~+85°C; 5%~95% RH Non condensing	
Dimension (L*W*H)	440*300*45mm	
Net /Gross Weight	<4.0kg / <4.8kg	<4.5kg / <5.2kg
Installation	Desktop type ,19 inch 1U cabinet installation	

Certification & Warranty


Lightning protection / protection level	Lightning protection: 6KV 8/20us; Protection level: IP30	
	IEC61000-4-2(ESD):±8kV contact discharge,±15kV air discharge	
	IEC61000-4-3(RS):10V/m(80~1000MHz)	
	IEC61000-4-4(EFT): power cable:±4kV; data cable:±2kV	
	IEC61000-4-5(Surge):power cable:CM±4kV/DM±2kV; data cable:±4kV	
	IEC61000-4-6(radio frequency transmission):10V(150kHz~80MHz)	
	IEC61000-4-8(power frequency magnetic field):100A/m;1000A/m ,1s to 3s	
	IEC61000-4-9(pulsed magnet field):1000A/m	
	IEC61000-4-10(damped oscillation):30A/m 1MHz	
	IEC61000-4-12/18(shockwave):CM 2.5kV,DM 1kV	
Mechanical Properties	IEC61000-4-16(common-mode transmission):30V; 300V,1s	
	FCC Part 15/CISPR22(EN55022):Class A	
	IEC61000-6-2(Common Industrial Standard)	
Certification	IEC60068-2-6 (anti vibration)	
	IEC60068-2-27 (anti shock)	
	IEC60068-2-32 (free fall)	
Warranty	5 years, lifelong maintenance.	

Network Management Features

Interface	IEEE802.3X (Full-duplex) Port temperature protection setting Port green Ethernet Energy-saving setting Broadcast storm control based on port speed The speed limit of the message flow in the access port. The minimum particle size is 64Kbps.
Layer 3 Features	L2+ network management ,IPV4/IPV6 management L3 soft routing forwarding, Static route, Default route @ 128 pcs, APR @ 1024 pcs
VLAN	4K VLAN based on port, IEEE802.1q VLAN based on the protocol VLAN based on MAC Voice VLAN, QinQ configuration Port configuration of Access, Trunk, Hybrid
Port Aggregation	LACP, Static aggregation Max 18 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)
Industrial Ring	G.8032 (ERPS),Recovery time less than 20ms
Network Protocol	250 Ring at most, Max 250 devices per ring.
Multicast	MLD Snooping v1/v2,Multicast VLAN IGMP Snooping v1/v2, Max 250 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS,Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)


ACL	Port-based Issuing ACL,ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection,Anti-DoS attack AAA & RADIUS,MAC learning limit Mac black holes,IP source protection IEEE802.1X & MAC address authentication Broadcast storm control,Backup for host datum SSH 2.0,SSL,Port isolation,ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client,DHCP Snooping, DHCP Server,DHCP Relay
Management	One-key recovery Cable Diagnose,LLDP Web Management (HTTPS) NTP,System work log,Ping Test CPU instant utilization status view Console/AUX Modem/Telnet/SSH2.0 CLI Download & Management on FTP, TFTP, Xmodem, SFTP,SNMP V1/V2C/V3 ONV NMS - smart network management system platform(LLDP+SNMP)
System	Category 5 Ethernet network cable Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later; TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network

DIMENSION



A.Working indicator	B. 8* PoE Ports
C. 24*Gigabit SFP Ports	D.4*1/10G SFP+ Ports
E.Console port	F.AC/DC dual input port

APPLICATION



ORDERING INFORMATION

Model	Description
ONV-IPS36368PFM	L2+ managed industrial PoE fiber switch with 8* 10/100/1000M RJ45 ports and 24*100/1000M SFP fiber slot ports and 4*1/10G SFP+ fiber slot ports, Port 1-8 can support IEEE802.3af/at PoE standard, Built-in 130W power supply. Support 1U/19 inch rack installation.
ONV-IPS36368PFM-at	L2+ managed industrial PoE fiber switch with 8* 10/100/1000M RJ45 ports and 24*100/1000M SFP fiber slot ports and 4*1/10G SFP+ fiber slot ports, Port 1-8 can support IEEE802.3af/at PoE standard, Built-in 250W power supply. Support 1U/19 inch rack installation.

Note: The SFP optical module is not included by default and needs to be purchased separately.

PACKING LIST

Packing List	CONTENT	QTY	UNIT
36-port 10G uplink managed industrial PoE fiber switch	1	SET	
AC Power Cable	1	PC	
Mounting Kits(Hanging Ear)	1	SET	
User Guide	1	PC	
Warranty Card	1	PC	

OPTICAL MODULE INFORMATION

Product	Model	Description	Unit
1.25G Optical Module	ONV-2630	SFP optical module, 1.25G, multi mode dual fiber 850nm, transmission distance: 550m, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-2632	SFP optical module, 1.25G, single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-2612-T	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-2613-R	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2612-T-G	Industrial SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	2613-R-G	Industrial SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-2612-T-SC	SFP optical module, 1.25G, single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface, support DDM function, support hot plug	PC

		and pull.	
	ONV-2613-R-SC	SFP optical module, 1.25G, single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface, support DDM function, support hot plug and pull.	PC
Power Module	ONV-2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.	PC
10G Optical Module	ONV-6630	SFP+ optical module, 10G Multi-mode dual fiber 850nm, transmission distance: 300m, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-7832	SFP+ optical module, 10G Single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-7832-33	SFP+ optical module, 10G Single-mode single fiber TX1330nm/RX1270nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC
	ONV-7832-27	SFP+ optical module, 10G Single-mode single fiber TX1270nm/RX1330nm, transmission distance: 20km, LC interface, support DDM function, support hot plug and pull.	PC

CONTACT US



OPTICAL NETWORK VIDEO TECHNOLOGIES (SHENZHEN) CO., LTD

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn

Website: www.onvcom.com

Zip: 518000

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen,
China

Factory Address: The 4-6th Floor, No. 59, Huaning Road, Xinwei Community, Dalang
Street, Longhua District, Shenzhen, China

