

## Product Datasheet

# 36-port 10G Uplink L3 Managed Industrial Ethernet Switch (ONV-IPS38368FM)



## OVERVIEW

The ONV-IPS38368FM is a 10G uplink L3 managed industrial Ethernet fiber switch independently developed by ONV. It has 8\*10/100/1000Base-T adaptive RJ45 ports and 24\*100/1000M uplink SFP fiber ports and 4\*1/10G uplink SFP+ fiber ports. Each port can support wire-speed forwarding.

The ONV-IPS38368FM has a L3 network management function to support IPV4/IPV6 management, dynamic routing full line-speed forwarding, complete security protection mechanism, perfect ACL/QoS policy, and rich VLAN functions easy to manage and maintain. With industry-leading ring network technology. It supports industrial-grade redundant ring network protocols, and each port can form a ring network, supporting chain ring network, starring network, double starring network, ring network, tangent network ring network, intersecting ring network, coupled ring network, self-healing within 20ms of the ring network. The ONV-IPS38368FM has high reliability, high security, and high manageability, ensures reliable transmission of key data, supports remote management, and cooperates with the ONV-NMS network management platform for cluster management to achieve no blind spot network management throughout the process. The ONV-IPS38368FM follows the industrial product design and materials. Galvanized steel metal shell enhances heat dissipation performance. It has excellent adaptability to the

industrial environment (including mechanical stability, climate environment adaptability, electromagnetic environment adaptability, etc.). Protection level reaches IP40 and supports 2AC+DC dual redundant power supply, 5 years warranty. It is suitable for intelligent transportation, rail transit, power industry, mining, petroleum, and industrial scenes such as shipping, metallurgy, and green energy construction forming a cost-effective stable, and reliable communication network.

## FEATURE

### ■ Full Gigabit line speed access, 10G uplink SFP+ port

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit Ethernet port and Gigabit SFP port and 10G SFP+ uplink port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

### ■ Strong business processing capability

- ◇ Support ERPS ring network and STP/RSTP/MSTP to eliminate layer 2 loops and realize link backup.
- ◇ Support IEEE802.1Q VLAN, Users can flexibly divide VLAN, Voice VLAN, and QinQ configuration according to their needs.
- ◇ Support static and dynamic aggregation to effectively increase link bandwidth, realize load balancing, link backup, and improve link reliability.
- ◇ Support QoS, port-based, 802.1P-based and DSCP-based three priority modes and four queue scheduling algorithms: Equ, SP, WRR, and SP+WRR.
- ◇ Support ACL to filter data packets by configuring matching rule processing operations and time permissions, and provide flexible security access control policies.
- ◇ Support IGMP V1/V2/V3 multicast protocol, IGMP Snooping meets multi-terminal high-definition video surveillance and video conference access requirements.

### ■ Security

- ◇ Port isolation, and storm control.
- ◇ IP+MAC+port+VLAN quadruple flexible combination binding function.
- ◇ 802.1X authentication provides authentication functions for LAN computers and controls the authorization status of controlled ports according to the authentication results.

#### ■ **Stable and reliable**

- ◇ CCC, CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR and Link.
- ◇ Adopt a self-developed power supply and redundant design to provide long-term stable power output.
- ◇ Low power consumption, no fan, galvanized steel metal shell, and aluminum alloy heat sink combination for super heat dissipation to ensure the stable operation of the switch.

#### ■ **Easy O&M management**

- ◇ Support CPU monitoring, memory monitoring, Ping detection, cable length detection.
- ◇ Support RMON, system log, and port traffic statistics to facilitate network optimization and transformation.
- ◇ Support HTTPS, SSLV3, SSHV1/V2 and other encryption methods, making management more secure.
- ◇ Support LLDP to facilitate the network management system to query and judge the communication status of the link.
- ◇ Support Web network management, CLI command line (Console, Telnet), SNMP (V1/V2/V3) and other diversified management and maintenance.

## TECHNICAL SPECIFICATION

Model	ONV-IPS38368FM
<b>Interface Characteristics</b>	
Fixed Port	1*Console port (115200,N,8,1) 2*AC100-240V power input ports Power off alarm switch port (FAULT) 4*1/10G uplink SFP+ fiber ports (Data) 8*10/100/1000Base-T RJ45 ports (Data) 24*100/1000Base-X uplink SFP fiber ports (Data) 2*DC12-48V power input ports ( support anti-reverse protection)
Ethernet Port	Port 1-8 support 10/100/1000Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meters) 100BASE-TX: Cat5 or later UTP (≤100 meters) 1000BASE-T: Cat5e or later UTP (≤100 meters)
Optical Fiber Port	1/10G SFP+ optical fiber port, default no include optical module (optional single-mode/ multi-mode, single fiber/ dual fiber optical module. LC)
SFP Port Expansion	Turbo overclocking 2.5G optical module expansion and ring network
Optical Cable/ Distance	Multi-mode: 850nm / 0~500m, 0~300M(10G), Single-mode: 1310nm / 0~ 40km, 1550nm / 0~120km.
<b>Chip Parameter</b>	
Network Management Type	L3
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3ae 10GBase-SR/LR, IEEE802.3x
Forwarding Mode	Store and Forward (Full Wire Speed)

Switching Capacity	176Gbps (non-blocking)
Forwarding Rate@64byte	107.14Mpps
CPU	500MHz
DRAM	2G
FLASH	128M
MAC	32K
Buffer Memory	32M
Jumbo Frame	9.6K
LED Indicator	Power: PWR (Yellow), System: SYS (Yellow) Network: Link/Act (Yellow), Fiber port: L/A (Green)
Reset Switch	Yes, press and hold the switch for 10 seconds and release it to restore the factory settings
<b>Power Supply</b>	
Total PWR / Input Voltage	60W (AC100-240V)
Power Consumption	Standby<35W, Full Load<50W
Power Supply	Built-in power supply, AC 100~240V 50-60Hz, 0.65A
Power Input Port	Alarm switch port, 2*AC power input ports, 2*DC12-48V input ports Dual input power port design: AC power supply priority to support anti-reverse connection protection, and automatically switches to DC connection when power fails.
<b>Physical Parameter</b>	
Operation TEMP / Humidity	-40~+80°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+85°C, 5%~95% RH Non condensing
Dimension (L*W*H)	440*298*44mm

Net /Gross Weight	3.95kg / 4.75kg
Installation	Desktop, 1U/19-inch cabinet
<b>Certification &amp; Warranty</b>	
Lightning Protection	Protection level: IP40
	Lightning protection: 6KV 8/20us
	IEC61000-4-3(RS):10V/m (80~1000MHz)
	FCC Part 15/CISPR22(EN55022): Class B
	IEC61000-6-2(Common Industrial Standard)
	IEC61000-4-9(Pulsed magnet field): 1000A/m
	IEC61000-4-10(Damped oscillation): 30A/m, 1MHz
	IEC61000-4-12/18(Shockwave): CM 2.5kV, DM 1kV
	IEC61000-4-4(EFT): Power cable:±4kV, Data cable: ±2kV
	IEC61000-4-16(Common-mode transmission): 30V, 300V, 1s
IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge	
IEC61000-4-6(Radio frequency transmission): 10V(150kHz~80MHz)	
IEC61000-4-8(Power frequency magnetic field):100A/m,1000A/m,1 to 3s	
IEC61000-4-5(Surge): Power cable: CM±4kV/DM±2kV, Data cable: ±4kV	
Mechanical Properties	IEC60068-2-6 (Anti vibration)
	IEC60068-2-32 (Free fall), IEC60068-2-27 (Anti shock)
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS
Warranty	5 years, lifelong maintenance.
<b>Network Management Feature</b>	
Interface	IEEE802.3X (Full-duplex)
	Port temperature protection setting
	No connection port automatic sleep
	Port green Ethernet Energy-saving setting
	Broadcast storm control based on port speed
	SFP+ optical port DDMI real-time digital diagnosis


	The speed limit of the message flow in the access port, mini particle size is 64Kbps.
Layer 3 Features	<p>IPv4 Equal Cost Routing</p> <p>NG protocol max 1000 entries</p> <p>ARP protocol max 1000 entries</p> <p>IPv4/IPv6 VRRP max group is 255</p> <p>Pingv6, Telnetv6, TFTPv6, DNSv6, ICMPv6</p> <p>IPv4/IPv6 VLANIF interface supports up to 128</p> <p>IPv4/IPv6 static route/ default route supports up to 128 entries</p> <p>IPv4 dynamic routing, RIPv1/v2, OSPFv2, BGP4+, 4000 routing entries</p> <p>IPv6 dynamic routing OSPFv3, BGP+, RIPv6, IPv6 management, 1000 routing entries</p> <p>L3 network management function, IPv4/IPv6 dual-stack management</p> <p>L3 routing and forwarding, support communication between different network segments and different VLAN</p>
VLAN	<p>Voice VLAN, QinQ configuration, IEEE802.1q</p> <p>VLAN based on MAC, VLAN based on the protocol</p> <p>4K VLAN based on port, Port configuration of Access, Trunk, Hybrid.</p>
Port Aggregation	<p>LACP dynamic aggregation, static aggregation</p> <p>Max 18 aggregation groups and 8 ports per group.</p>
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Industrial Ring	250 Ring at most, Max 250 devices per ring.
Network Protocol	G.8032 (ERPS), Recovery time less than 20ms
Multicast	<p>IGMP Snooping v1/v2, Max 1024 multicast groups</p> <p>MLD Snooping v1/v2, Multicast VLAN, Fast log out</p>
Port Mirroring	Bidirectional data mirroring based on port
QoS	<p>Diff-Serv QoS, Priority Mark/Remark</p> <p>Queue Scheduling Algorithm (SP, WRR, SP+WRR)</p> <p>Flow-based Rate Limiting, Flow-based Packet Filtering</p>

	8*Output queues of each port, 802.1p/DSCP priority mapping
ACL	<p>Port-based Issuing ACL, ACL based on port and VLAN</p> <p>L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.</p>
Security	<p>IP source address protection</p> <p>ARP intrusion detection function</p> <p>ARP message rate limiting function</p> <p>Port broadcast message suppression</p> <p>SSL ensures data transmission security</p> <p>AAA &amp; RADIUS &amp; TACACS+ certification</p> <p>Anti-DoS attack, MAC address black hole</p> <p>Limit the number of MAC addresses learned</p> <p>Port isolation, Host data backup mechanism</p> <p>Quadruple binding function of IP+MAC+VLAN+port</p> <p>User hierarchical management and password protection</p> <p>SSH 2.0 provides a secure encrypted channel for user login</p> <p>IEEE802.1X authentication/ centralized MAC address authentication</p>
DHCP	DHCP Client, DHCP Snooping, DHCP Server, DHCP Relay
Management	<p>NTP clock, Cable length detection</p> <p>View CPU real-time utilization status</p> <p>One click recovery, SNMP V1/V2/V3</p> <p>System work log, Link Layer Discovery Protocol</p> <p>Ping detection, Web network management (HTTPS)</p> <p>ONV-NMS platform cluster management (LLDP+SNMP)</p> <p>FTP, TFTP, Xmodem, SFTP file upload and download management</p> <p>Console/ AUX Modem/ Telnet/ SSH2.0 CLI command line configuration</p>
System	<p>Web browser: Mozilla Firefox 2.5 or higher, Google Chrome V42 or higher,</p> <p>Cat5 and above Ethernet cable</p>




TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, Mac OS X) installed on each computer in the network  
 Cat5 and above Ethernet cable

## DIMENSION



## APPLICATION



## ORDERING INFORMATION

Model	Description	Recommended Power Supply
ONV-IPS36368FM	L3 managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 24*100/1000M uplink SFP fiber ports and 4*1/10G uplink SFP+ fiber ports. It supports 2AC and DC power terminal input and 1U/19-inch cabinet installation.	2*60W

**Note:** The optical module is not included need to be purchased separately.

## PACKING LIST

	Content	Qty	Unit
Packing List	36-port 10G uplink L3 managed industrial Ethernet switch	1	SET
	AC Power Cable	1	PC
	Mounting Kits (Hanging Ear)	1	SET
	User Guide	1	PC
	Warranty Card	1	PC

## OPTICAL MODULE

Product	Model	Description	Unit
1.25G Optical Module	2630-G	Industrial SFP optical module, 1.25G multi-mode dual fiber 850nm, transmission distance: 550m, LC interface, supports DDM function and hot plugging.	PC
	2632-G	Industrial SFP optical module, 1.25G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, supports DDM function and hot plugging.	PC
	2612-T-G	Industrial SFP optical module, 1.25G single-mode single fiber	PC

		TX1310nm/ RX1550nm, transmission distance: 20km, LC interface, supports DDM function and hot plugging.	
	2613-R-G	Industrial SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, LC interface, supports DDM function and hot plugging.	PC
	2612-T-G-SC	Industrial SFP optical module, 1.25G single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, SC interface, supports DDM function and hot plugging.	PC
	2613-R-G-SC	Industrial SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, SC interface, supports DDM function and hot plugging.	PC
10G Optical Module	6630-G	Industrial SFP+ optical module, 10G multi-mode dual fiber 850nm, transmission distance: 300m, LC interface, supports DDM function and hot plugging.	PC
	7832-G	Industrial SFP+ optical module, 10G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface, supports DDM function and hot plugging.	PC
	7832-33-G	Industrial SFP+ optical module, 10G single-mode single fiber TX1330nm/ RX1270nm, transmission distance: 20km, LC interface, supports DDM function and hot plugging.	PC
	7832-27-G	Industrial SFP+ optical module, 10G single-mode single fiber TX1270nm/ RX13300nm, transmission distance: 20km, LC interface, supports DDM function and hot plugging.	PC

## RELATED PRODUCT

Model	Description
ONV-IPS33018FM	L2+ managed industrial Ethernet fiber switch has 16*10/100/1000M RJ45 ports and 2 *100/1000M uplink SFP fiber ports. It built-in redundant

	dual power supply and supports 2AC+DC power terminal input and 1U/19-inch cabinet installation.
ONV-IPS33026FM	L2+ managed industrial Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 4*100/1000M uplink SFP fiber ports (combo ports). It built-in redundant dual power supply and supports 2AC+DC power terminal input and 1U/19-inch cabinet installation.
ONV-IPS38028FM	L3 managed industrial Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 4*1/10G uplink SFP+ fiber ports. It built-in redundant dual power supply and supports 2AC+DC power terminal input and 1U/19-inch cabinet installation.
ONV-IPS38048FM	L3 managed industrial Ethernet fiber switch with 48*10/100/1000M RJ45 ports and 4*1/10G uplink SFP+ fiber ports. It built-in redundant dual power supply and supports 2AC+DC power terminal input and 1U/19-inch cabinet installation.
ONV-IPS38036FM	L3 managed industrial Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 8*100/1000M uplink SFP fiber ports and 4*1/10G SFP+ slot ports. It built-in redundant dual power supply and supports 2AC+DC power terminal input and 1U/19-inch cabinet installation.
ONV-IPS38448FM	L3 managed industrial Ethernet fiber switch with 12*10/100/1000M RJ45 ports and 28*100/1000M uplink SFP fiber ports and 4*1/10G uplink SFP+ fiber ports. It built-in redundant dual power supply and supports 2AC+DC power terminal input and 1U/19-inch cabinet installation.

## CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

WeChat: ONV-PoE-IoT

Email: onv@onv.com.cn

Skype: [onv@onv.com.cn](mailto:onv@onv.com.cn)

Website: [www.onvcom.com](http://www.onvcom.com)

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen,  
China

Factory Address: Floor 4-6, Building A, Senyutai Industrial Park, No. 111, Huaning Road,  
Xinshi Community, Dalang Street, Longhua District, Shenzhen, China

