

Product Datasheet

28-port Full Gigabit Cloud Managed PoE Switch (ONV-POE53028PFCM)



OVERVIEW

The ONV-POE53028PFCM is a full Gigabit L2 managed PoE switch independently developed by ONV. It has 4*10/100/1000Base-T uplink RJ45 and 4*1000Base-X uplink SFP fiber combo ports and 24*10/100/1000Base-T adaptive RJ45 ports. Port 1-24 can support IEEE 802.3 af/at PoE standard and single-port PoE power up to 30W. As a PoE power supply device, it can automatically detect and identify powered devices that meet standards and power them through network cables. It can supply power to POE terminal equipment such as wireless AP, IP camera, Internet phone, video door intercom, etc. through a network cable to meet the network environment that requires a high-density PoE power supply. It is suitable for hotels, campuses, factory dormitories, and SMB small and medium-sized enterprises, and cost-effective networking.

The ONV-POE53028PFCM can support Web management and ONV-NMS management platform and cloud management APP management to realize security network storm control, port management, VLAN configuration, remote operation and maintenance, and other functions. It has high reliability, is easy to install and maintain, has fast switching functions, and multiple access ports, and is suitable for accessing LAN devices of various sizes.

FEATURE

■ Gigabit access, uplink RJ45/SFP combo port

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit Ethernet port and Gigabit RJ45/SFP combo port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

■ Smart PoE power supply

- ◇ Remote PoE management function, port remote opening and closing.
- ◇ Comply with IEEE 802.3 af/at PoE standard, automatically identify PoE devices for power supply, and not damage non-PoE devices.
- ◇ 24*10/100/1000Base-T RJ45 ports can support PoE power to meet the needs of security monitoring, teleconferencing system, wireless coverage, and other scenarios.

■ Extreme optimization, minimalist application

- ◇ Real-time fault alarm and fault location.
- ◇ Remote upgrade, remote restart, and factory reset.
- ◇ Local platform, cloud platform and mobile APP operation and maintenance management.
- ◇ Visual network topology management, VLAN division, PoE control, port control, and switching capacity management.
- ◇ Practical network management functions are retained according to industry application requirements, and network deployment and centralized operation and maintenance can be quickly realized through the operation and maintenance platform.

■ Innovative features

- ◇ Switch **E** to the ON position, and port 16-24 support 10M/250 meters transmission.
- ◇ Switch **W** to the ON position, turn on the network management function, enter the network management interface, and configure the required functions of the switch. After this function is turned on, all other dialing functions will be invalid and must be

configured separately through management.

- ◇ Switch **V** to the ON position. Port 1-24 supports the watchdog function and automatically detects data communication status in real time. When port communication fails, the corresponding port PoE will automatically restart. Port 1-24 supports physical VLAN isolation functions to suppress broadcast storms. , improve network performance.
- ◇ Switch **B** to the ON position, and the storm suppression function will start port monitoring and implement traffic suppression and storm control, thereby limiting the traffic to a reasonable range and solving the problem of a large number of broadcast, multicast, multicast, and unicast (including unknown unicast) in the network.) data frames cause problems such as network slowdown, data transmission timeout, data transmission congestion, and massive packet loss.

■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ The user-friendly pane can show the device status through the LED indicator of PWR, SYS, Link, L/A, and PoE.
- ◇ Low power consumption, with fan, galvanized steel casing, and excellent heat dissipation ensures the stable operation of the switch.

TECHNICAL SPECIFICATION


Model	ONV-POE53028PFCM	ONV-POE53028PFCM-at
Interface Characteristics		
Fixed Port	24*10/100/1000Base-T PoE ports (Data/ Power) 4*10/100/1000Base-T uplink RJ45 ports (Data) 4*1000Base-X uplink SFP fiber cmobo ports (Data)	
Ethernet Port	Port 1-24 support 10/100/1000Base-T auto-sensing, full/ half duplex MDI/ MDI-X self-adaption	
Twisted Pair	10BASE-T: Cat3,4,5 UTP (≤100 meters)	

Transmission	100BASE-TX: Cat5 or later UTP (≤100 meters) 1000BASE-T: Cat5e or later UTP (≤100 meters)	
Optical Fiber Port	Gigabit optical fiber interface, default no included optical module (optional single-mode/ multi-mode, single fiber/ dual fiber optical module. LC)	
Optical Cable/ Distance	Multi-mode: 850nm/ 0-500m Single-mode: 1310nm/ 0-40km, 1550nm/ 0-120km.	
Chip Parameter		
Network Management Type	L2 (Web management, platform management)	
Network Protocol	IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3z 1000Base-X, IEEE 802.3x	
Forwarding Mode	Store and Forward (Full wire-speed)	
Switching Capacity	56Gbps (Non-blocking)	
Forwarding Rate@64byte	41.66Mpps	
MAC	8K	
Buffer Memory	4M	
Jumbo Frame	10K	
LED Indicator	Power: PWR (Green), System: SYS (Green), Network: Link (Green), PoE: PoE (Red), Fiber port: L/A (Green)	
Reset Switch	Press and hold RESET for 10 seconds and then release to restore factory default settings.	
PoE & Power Supply		
PoE Port	Port 1-24	
PoE Management	Remote PoE port on/off, port power allocation, real-time view of PoE status	
Power Supply Pin	1/2(+) 3/6 (-)	
Max Power Per Port	30W, IEEE 802.3 af/at	
Total PWR / Input Voltage	400W/ (AC100-240V)	600W/ (AC100-240V)

Power Consumption	Standby<16W, Full Load<400W	Standby<16W, Full Load<600W
Power Supply	Built-in power supply, AC100~240V 50-60Hz, 5.0A	Built-in power supply, AC100~240V 50-60Hz, 6.6A
Physical Parameter		
Operation TEMP/ Humidity	-40°C~+75°C, 5%~90% RH Non condensing	
Storage TEMP/ Humidity	-40°C~+85°C, 5%~95% RH Non condensing	
Dimension (L*W*H)	440*270*44mm	
Net /Gross Weight	3.8kg /4.7kg	4.1kg /5.1kg
Installation	Desktop, wall mount, 1U/19" cabinet	
Certification & Warranty		
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30	
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS	
Warranty	3 years, lifelong maintenance.	
Network Management Feature		
Interface	Port status display, Port traffic statistics Port duplex/ negotiation rate configuration EEE Energy-saving and green Ethernet function IEEE802.3x flow control configuration (Full-duplex)	
VLAN	Port-based IEEE802.1Q VLAN configuration (4K)	
Security	Broadcast storm suppression	
Management	One-key recovery, Web Management Mobile APP operation and maintenance management ONV-NMS platform management (Local platform/ Cloud platform)	
System	Web browser: Mozilla Firefox 2.5 or higher, Google Chrome V42 or higher, Cat5 and above Ethernet cable	

TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, Mac OS X) installed on each computer in the network Cat5 and above Ethernet cable

DIMENSION



APPLICATION

ORDERING INFORMATION

Model	Description	Built-in Power Supply
ONV-POE53028PFCM	L2 Easy managed PoE switch with 24*10/100/1000M RJ45 ports and 4*10/100/1000M RJ45 ports and 4*1000M uplink SFP fiber combo ports. Port 1-24 can support	400W
ONV-POE53028PFCM-at	IEEE 802.3 af/at PoE standard. It built-in power supply and desktop and 1U/19" cabinet mount.	600W

Note: The optical module is not included and needs to be purchased.

PACKING LIST

	Content	Qty	Unit
Packing List	28-port full gigabit cloud managed PoE switch	1	SET
	AC Power Cable	1	PC
	User Guide	1	PC
	Warranty Card	1	PC

OPTICAL MODULE

Product	Model	Description	Unit
1.25G Optica Module	2630	SFP optical module, 1.25G multi-mode dual fiber 850nm, transmission distance: 550m, LC interface. support DDM function and hot plugging.	PC
	2632	SFP optical module, 1.25G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface. support DDM function and hot plugging.	PC
	2612-T	SFP optical module, 1.25G single-mode single fiber TX1310nm/	PC

		RX1550nm, transmission distance: 20km, LC interface. support DDM function and hot plugging.	
	2613-R	SFP optical module, 1.25G single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, LC interface. support DDM function and hot plugging.	PC
	2612-T-SC	SFP optical module, 1.25G single-mode single fiber TX1310nm/RX1550nm, transmission distance: 20km, SC interface. support DDM function and hot plugging.	PC
	2613-R-SC	SFP optical module, 1.25G single-mode single fiber TX1550nm/RX1310nm, transmission distance: 20km, SC interface. support DDM function and hot plugging.	PC
Power Module	2633	1.25G SFP optical module transfers to 10/100/1000M RJ45 port.	PC

CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn

Skype: onv@onv.com.cn

WeChat ID: ONV-PoE-IoT

Website: www.onvcom.com

Address: Room 10D03, Shenye Tairan Building, No. 8 Tairan Road, Tianan Community, Shatou Street, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333, Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou