

Product Datasheet

16-port Full Gigabit Managed Industrial Ethernet Switch (ONV-IPS53168FM)



OVERVIEW

The ONV-IPS53168FM is a Gigabit L2+ managed industrial Ethernet fiber switch independently developed by ONV. It has 8*10/100/1000Base-T adaptive RJ45 ports and 8*100/1000Base-X uplink SFP fiber ports. Each port support wire-speed forwarding.

The ONV-IPS53168FM has L2+ network management functions, supports IPV4/IPV6 management, static route forwarding, complete security protection mechanisms, complete ACL/QoS policies, and rich VLAN functions for easy management and maintenance. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS (<20ms) to improve link backup and network reliability. Communication can be quickly restored when a one-way network fails. Ensure uninterrupted communication for important applications. According to the application needs, the port management, routing address management, port flow control, VLAN division, IGMP,

security policy, and other application business configurations are performed through network management methods such as Web, CLI, SNMP, and Telnet. The ONV-IPS53168FM follows industrial product design and materials. The outer shell is made of aluminum alloy to enhance heat dissipation performance and has excellent industrial site environmental adaptability (mechanical stability, climate environment adaptability, electromagnetic environment adaptability, etc.). It is suitable for establishing cost-effective, stable, and reliable communication networks in industrial scenarios such as intelligent transportation, rail transportation, power industry, mining, petroleum, shipping, metallurgy, and green energy construction.

FEATURE

■ Gigabit access, uplink SFP fiber port

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit RJ45 port and Gigabit SFP port combination, which enables users to flexibly build networking to meet the needs of various scenarios.

■ Strong business processing capability

- ◇ Support Industrial ERPS ring network and STP/RSTP/MSTP to eliminate layer 2 loops and realize link backup.
- ◇ Support IEEE802.1Q VLAN, Users can flexibly divide VLAN, Voice VLAN, and QinQ configuration according to their needs.
- ◇ Support static and dynamic aggregation to effectively increase link bandwidth, realize load balancing, link backup, and improve link reliability.
- ◇ Support QoS, port-based, 802.1P-based, and DSCP-based three priority modes and four queue scheduling algorithms: Equ, SP, WRR, and SP+WRR.
- ◇ Support ACL to filter data packets by configuring matching rule processing operations and time permissions, and provide flexible security access control policies.
- ◇ Support IGMP V1/V2/V3 multicast protocol, IGMP Snooping meets multi-terminal

high-definition video surveillance and video conference access requirements.

■ Security

- ◇ Port isolation and storm control.
- ◇ IP+MAC+port+VLAN quadruple flexible combination binding function.
- ◇ 802.1X authentication provides authentication functions for LAN computers, and controls the authorization status of controlled ports according to the authentication results.

■ Stable and reliable

- ◇ CCC, CE, FCC, and RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR, SYS, Link, and L/A.
- ◇ Low power consumption, no fan, aluminum shell, excellent heat dissipation to ensure the stable operation of the switch.

■ Easy O&M management

- ◇ Support CPU monitoring, memory monitoring, Ping detection, and cable length detection.
- ◇ HTTPS, SSLV3, SSHV1/V2, and other encryption methods are more secure in management.
- ◇ RMON, system log, and port traffic statistics are convenient for network optimization and transformation.
- ◇ LLDP is convenient for the network management system to query and judge the communication status of the link.
- ◇ Support diverse management and maintenance methods such as Web network management, CLI command line (Console, Telnet), SNMP (V1/V2/V3), Telnet, etc.

TECHNICAL SPECIFICATION

| Model | ONV-IPS53168FM |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Interface Characteristics | |
| Fixed Port | 1*RS232 console port (115200, N, 8,1) 1*Power failure alarm switch port (FAULT) 8*10/100/1000Base-T RJ45 ports (Data) 8*100/1000Base-X uplink SFP fiber ports (Data) 2*DC12-48V input ports (supports reverse connection protection) |
| Ethernet Port | Port 1-8 support 10/100/1000Base-T(X) auto-sensing, full/ half duplex MDI/ MDI-X self-adaption |
| Twisted Pair Transmission | 10BASE-T: Cat3,4,5 UTP (≤100 meters) 100BASE-TX: Cat5 or later UTP (≤100 meters) 1000BASE-T: Cat5e/6 or later UTP (≤100 meters) |
| Optical Fiber Port | Default no include optical module (optional single-mode/ multi-mode, single fiber/ dual fiber optical module. LC) |
| Optical Port Expansion | Turbo overclocking 2.5G optical module expansion and ring network |
| Optical Cable/ Distance | Multi-mode: 850nm/ 0-500m (1G), Single-mode: 1310nm/ 0-40km, 1550nm/ 0-120km |
| Chip Parameter | |
| Network Management Type | L2+ |
| Network Protocol | IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3z 1000Base-X, IEEE 802.3x |
| Forwarding Mode | Store and Forward (Full Wire Speed) |
| Switching Capacity | 128Gbps (non-blocking) |
| Forwarding Rate@64byte | 23.81Mpps |

| | |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CPU | 800MHz |
| DRAM | 1Gb |
| FLASH | 128Mb |
| MAC | 16K |
| Buffer Memory | 12Mb |
| Jumbo Frame | 12KB |
| LED Indicator | System: SYS (Green), Network: Link (Yellow), Fiber port: L/A (Green) |
| Reset Switch | Yes, press and hold the switch for 10 seconds and release it to restore the factory settings |
| Power Supply | |
| Power Consumption | Standby<8W, Full load <15W |
| Working Voltage | DC12-48V, 6 Pin industrial Phoenix terminal, support anti-reverse protection. |
| Power Supply | No, optional 24V/24W industrial power supply |
| Physical Parameter | |
| Operation TEMP /Humidity | -40~+75°C, 5%~90% RH Non condensing |
| Storage TEMP /Humidity | -40~+80°C, 5%~95% RH Non condensing |
| Dimension (L*W*H) | 166*150*75mm |
| Net /Gross Weight | 1.8kg / 2.1kg |
| Installation | Desktop, 35mm DIN Rail |
| Certification & Warranty | |
| Lightning Protection | Protection level: IP40 Lightning protection: 6KV 8/20us IEC61000-4-3 (RS):10V/m (80~1000MHz) FCC Part 15/CISPR22 (EN55022): Class B IEC61000-6-2 (Common Industrial Standard) IEC61000-4-9 (Pulsed magnet field): 1000A/m |

| | |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>IEC61000-4-10 (Damped oscillation): 30A/m, 1MHz</p> <p>IEC61000-4-12/18 (Shockwave): CM 2.5kV, DM 1kV</p> <p>IEC61000-4-4(EFT): Power cable:±4kV, Data cable: ±2kV</p> <p>IEC61000-4-16 (Common-mode transmission): 30V, 300V, 1s</p> <p>IEC61000-4-2 (ESD): ±8kV contact discharge, ±15kV air discharge</p> <p>IEC61000-4-6 (Radio frequency transmission): 10V(150kHz~80MHz)</p> <p>IEC61000-4-8 (Power frequency magnetic field):100A/m, 1000A/m, 1s-3s</p> <p>IEC61000-4-5 (Surge): Power cable: CM±4kV/ DM±2kV, Data cable: ±4kV</p> |
| Mechanical Properties | IEC60068-2-6 (Anti Vibration), IEC60068-2-32 (Free Fall), IEC60068-2-27 (Anti Shock) |
| Certification | CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS |
| Warranty | 5 years, lifelong maintenance. |
| Network Management Feature | |
| Interface | <p>IEEE802.3x flow control (Full duplex)</p> <p>Port exception protection mechanism</p> <p>Port real-time flow management (Flow Interval)</p> <p>Broadcast storm suppression based on port rate</p> <p>Jumbo frame configuration, the largest 12000byte</p> <p>Optical port SFP module DDMI real-time digital diagnosis</p> <p>Port EEE Green Ethernet Energy-Saving configuration and status view</p> <p>Limit the rate of incoming and outgoing packet traffic, with mini granularity of 16Kbps and max of 1Gbps</p> |
| L3 Features | <p>ARP protocol, max 1024 entries</p> <p>IPv4/IPv6 static route, max 128 entries</p> <p>L2+ network management function, dual-stack IPv4/IPv6 management</p> |
| VLAN | <p>VLAN based on MAC, VLAN based on the protocol</p> <p>Port configuration of Access, Trunk, Hybrid. GVRP VLAN protocol</p> <p>(4K) VLAN based on port, IEEE802.1q, Voice VLAN, QinQ configuration</p> |

| | |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Port Aggregation | LACP, Static aggregation Max 8 aggregation groups and max 8 ports per group. |
| Spanning Tree | STP BPDU Guard, BPDU filtering and BPDU forwarding STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s) |
| ERPS Ring Network | Support ERPS ring network, Recovery time less than 20ms, ITU-T G.8032 |
| Multicast | MLD Snooping, Multicast VLAN User quick log out, MVR (Multicast VLAN Registration) IGMP Snooping v1/v2/v3 and 1024 multicast groups at most |
| Mirroring | Bidirectional traffic mirroring for basic ports one-to-multiple mirroring, supports up to 4 port sessions |
| QoS | Queue Scheduling Algorithm (SP, WRR, SP+WRR) Flow-based Rate Limiting, Stream based redirection Flow-based Packet Filtering, 8*Output queues of each port 802.1p/ DSCP priority mapping, Diff-Serv QoS, Priority Mark/ Remark |
| ACL | ACL distribution based on port and VLAN L2-L4 packet filtering function, matching the first 80 bytes message, and provides ACL definitions based on source MAC address, destination MAC address, source IP address, destination IP address, IP protocol type, TCP/UDP port, TCP/UDP port range, VLAN, etc. |
| Security | Port based IEEE802.1X authentication SSL guarantees data transmission security Quad binding function of IP+MAC+VLAN+ports MAC address learning limit, MAC address black hole Anti DoS attack, Port broadcast message suppression IP Source Guard function, AAA&RADIUS certification Hierarchical user management and password protection SSH 2.0 provides a secure encrypted channel for user login Host data backup mechanism, ARP intrusion detection function Port isolation, IP Source Guard, ARP message speed limit function |

| | |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DHCP | DHCP Client, DHCP Snooping, DHCP Server |
| Management | <p>Web network management (https)</p> <p>Link Layer Discovery Protocol(LLDP)</p> <p>Viewing CPU Instant Utilization Status</p> <p>NTP clock, One click restore, SNMP V1/V2/V3</p> <p>Cable status check, Ping detection, System work log</p> <p>ONV-NMS platform cluster management (LLDP+SNMP)</p> <p>Console/ AUX Modem/ Telnet/ CLI command line configuration</p> <p>FTP, TFTP, Xmodem, SFTP file upload and download management</p> |
| System | <p>Web browser: Mozilla Firefox 2.5 or higher, Google Chrome V42 or higher,</p> <p>Cat5 and above Ethernet cable</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, Mac OS X) installed on each computer in the network</p> <p>Cat5 and above Ethernet cable</p> |

DIMENSION

APPLICATION

ORDERING INFORMATION

| Model | Description | Recommended Power Supply |
|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| ONV-IPS53168FM | L2+ managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 8*100/1000M uplink SFP fiber ports. It can support dual DC power supply input and DIN rail mounting. | 24W/36W |

Note: The optical module and power supply are not included and need to be purchased.

PACKING LIST

| | Content | Qty | Unit |
|--------------|----------------------------------------------------|-----|------|
| Packing List | 16-port Gigabit managed industrial Ethernet switch | 1 | SET |
| | RJ45-DB9 adapter conversion Line | 1 | PC |
| | User Guide | 1 | PC |
| | Warranty Card | 1 | PC |

OPTICAL MODULE

| Product | Model | Description | Unit |
|----------------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 1.25G Optical Module | 2630-G | Industrial SFP optical module, 1.25G multi-mode dual fiber 850nm, transmission distance: 550m, LC interface. supports DDM function and hot plugging. | PC |
| | 2632-G | Industrial SFP optical module, 1.25G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging. | PC |
| | 2612-T-G | Industrial SFP optical module, 1.25G single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging. | PC |
| | 2613-R-G | Industrial SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging. | PC |
| | 2612-T-G-SC | Industrial SFP optical module, 1.25G single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, SC interface. supports DDM function and hot plugging. | PC |
| | 2613-R-G-S C | Industrial SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, SC interface. supports DDM function and hot plugging. | PC |

POWER SUPPLY

| Product | Model | Description | Unit |
|--------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 24W DIN Rail Industrial Power Supply | GWS-DP24-24 | DIN Rail 24W single set of output power supply Input Voltage: AC100V-240V 50-60Hz, 0.35A Output Voltage: DC24V, 1.0A Operation Temperature: -40°C to +70°C | PC |
| 36W DIN Rail Industrial Power Supply | GWS-DP36-24 | DIN Rail 36W single set of output power supply Input Voltage: AC100V-240V 50-60Hz, 0.56A Output Voltage: DC24V, 1.5A Operation Temperature: -40°C to +70°C | PC |

CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

WeChat: ONV-PoE-IoT

Email: onv@onv.com.cn

Skype: onv@onv.com.cn

Website: www.onvcom.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333,

Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou

