

## Product Datasheet

# 8-port Gigabit Easy Managed Industrial Ethernet Switch (ONV-IPS53008M)



## OVERVIEW

The ONV-IPS53008M is a Gigabit Easy managed industrial Ethernet switch independently developed by ONV. It has 8\*10/100/1000Base-T adaptive RJ45 ports. Each port can support wire-speed forwarding.

The ONV-IPS53008M can support Web management, ONV-NMS management platform, and mobile APP cloud platform management, which can realize functions such as security network topology management, link aggregation, port management, port mirroring, and remote operation and maintenance. The switch has high reliability, easy installation and maintenance, a fast switching function, and multiple access ports, which are suitable for

access to LAN devices of various scales. It is suitable for intelligent transportation, rail transportation, electric power industry, mining, petroleum, shipping, metallurgy green energy construction, and other industrial scenarios to build an economical, efficient, stable, and reliable communication network.

## FEATURE

### ■ Gigabit access, full wire-speed forwarding

- ◇ Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- ◇ Support non-blocking wire-speed forwarding for smoother transmission, meeting the networking requirements of various scenarios

### ■ Extreme Optimization, minimalist application

- ◇ Real-time fault alarm and fault location.
- ◇ Remote upgrade, remote restart, and factory reset.
- ◇ Local platform, cloud platform, and mobile APP operation and maintenance management.
- ◇ Visual network topology management, VLAN division, port control, and switching capacity management.
- ◇ Practical network management functions are retained according to industry application requirements, and network deployment and centralized operation and maintenance can be quickly realized through the operation and maintenance platform.

### ■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR and SYS.
- ◇ Low power consumption, no fan, Aluminum alloy housing, and excellent heat dissipation to ensure the stable operation of the switch.


## TECHNICAL SPECIFICATION

Model	ONV-IPS53008M
<b>Interface Characteristics</b>	
Fixed Port	1*DC5521 power socket 8*10/100/1000Base-T RJ45 ports (Data) 2 sets V+, V- redundant DC power port (5P phoenix terminal)
Ethernet Port	Port 1-8 can support 10/100/1000Base-T auto-sensing, full/ half duplex MDI/MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meters) 100BASE-TX: Cat5 or later UTP (≤100 meters) 1000BASE-T: Cat5e or later UTP (≤100 meters)
<b>Chip Parameter</b>	
Network Management Type	L2 (Web management, platform management)
Network Protocol	IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3x
Forwarding Mode	Store and Forward (Full wire-speed)
Switching Capacity	16Gbps (non-blocking)
Forwarding Rate @64byte	11.90Mpps
MAC	8K
Buffer Memory	2M
Jumbo Frame	9.2K
LED Indicator	Power/ System: SYS (Green), Network: Link (Yellow)
Reset Switch	Press for 6 seconds and then release to restore to factory settings Short press twice (1 second interval) to switch to unmanaged state
<b>Power Supply</b>	
Power Consumption	Standby<3W, Full load<6W

Working Voltage	DC12-48V, 5P industrial phoenix terminal, anti-reverse protection
Power Supply	No, optional 12V/24W or 24V/24W industrial power supply
<b>Physical Parameter</b>	
Operation Temp/ Humidity	-40~+75°C, 5%~90% RH Non condensing
Storage Temp/ Humidity	-40~+85°C, 5%~95% RH Non condensing
Dimension (L*W*H)	116*84*40mm
Net /Gross Weight	0.35kg/ 0.45kg
Installation	Desktop, 35mm DIN Rail
<b>Certification &amp; Warranty</b>	
Lightning Protection	Protection level: IP40
	Lightning protection: 6KV 8/20us
	IEC61000-4-3 (RS):10V/m (80~1000MHz)
	FCC Part 15/CISPR22 (EN55022): Class B
	IEC61000-6-2 (Common Industrial Standard)
	IEC61000-4-9 (Pulsed magnet field): 1000A/m
	IEC61000-4-10 (Damped oscillation): 30A/m, 1MHz
	IEC61000-4-12/18 (Shockwave): CM 2.5kV, DM 1kV
	IEC61000-4-4(EFT): Power cable:±4kV, Data cable: ±2kV
	IEC61000-4-16 (Common-mode transmission): 30V, 300V, 1s
	IEC61000-4-2 (ESD): ±8kV contact discharge, ±15kV air discharge
	IEC61000-4-6 (Radio frequency transmission): 10V(150kHz~80MHz)
	IEC61000-4-8 (Power frequency magnetic field):100A/m, 1000A/m, 1s-3s
IEC61000-4-5 (Surge): Power cable: CM±4kV/ DM±2kV, Data cable: ±4kV	
Mechanical Properties	IEC60068-2-6 (Anti Vibration), IEC60068-2-32 (Free Fall), IEC60068-2-27 (Anti Shock)
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS

Warranty	5 years, lifelong maintenance.
<b>Network Management Feature</b>	
Interface	EEE Energy-saving and green Ethernet function Port status display, Port duplex/negotiation rate configuration IEEE802.3x flow control configuration (Full-duplex), Port traffic statistics
VLAN	Port-based IEEE802.1Q VLAN configuration (4K)
Port Aggregation	Static aggregation
Loop Protection	Loop protection function
Multicast	IGMP Snooping v1/v2, Max 256 multicast groups
Port Mirroring	Bidirectional data mirroring based on port
QoS	Diff-Serv QoS, 8*Output queues of each port, 802.1p/DSCP priority mapping, Priority Mark/Remark
Security	Broadcast storm control, Port isolation, Port speed limit
DHCP	DHCP Snooping
Management	Mobile APP operation and maintenance management One-key recovery, Cable Diagnose, Web Management (https) ONV-NMS platform management (Local platform/Cloud platform)
System	Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Category 5 and above Ethernet cables TCP/IP, network adapter, and network operating systems (Such as Microsoft Windows, Linux or Mac OS X) are installed on each computer in the network with Category 5 and above Ethernet cables

## DIMENSION



## ORDERING INFORMATION

Model	Description	Recommended Power Supply
ONV-IPS53008M	Easy managed industrial Ethernet switch with 8*10/100/1000M RJ45 ports. It can support dual DC power supply input and DIN Rail mounting.	24W

**Note:** The power supply is not included and needs to be purchased.

## PACKING LIST

Packing List	Content	Qty	Unit
	8-port gigabit Easy managed industrial Ethernet switch	1	SET
	User Guide	1	PC
	Warranty Card and Certificate of Conformity	1	PC

## POWER SUPPLY

Product	Model	Description	Unit
24W DIN Rail Industrial Power Supply	GWS-DP24-12	DIN Rail 24W single set of output power supply Input Voltage: AC100V~240V 50-60H, 0.35A Output Voltage: DC12V, 2.0A Operation Temperature: -40°C to +70°C	PC
24W DIN Rail Industrial Power Supply	GWS-DP24-24	DIN Rail 24W single set of output power supply Input Voltage: AC100V~240V 50-60H, 0.35A Output Voltage: DC24V, 1.0A Operation Temperature: -40°C to +70°C	PC

## RELATED PRODUCT

Model	Description
ONV-IPS53064FM	Easy managed industrial Ethernet fiber switch with 4*10/100/1000M RJ45 ports and 2*100/1000M uplink SFP fiber ports. It can support dual DC power supply input and DIN Rail mounting.
ONV-IPS53064FGM	Easy managed industrial Ethernet fiber switch with 5*10/100/1000M RJ45 ports and 1*100/1000M uplink SFP fiber port. It can support dual DC power supply input and DIN Rail mounting.
ONV-IPS53108FM	Easy managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 2*100/1000M uplink SFP fiber ports. It can support dual DC power supply input and DIN Rail mounting.

## CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

WeChat: ONV-PoE-IoT

Email: [onv@onv.com.cn](mailto:onv@onv.com.cn)

Skype: [onv@onv.com.cn](https://www.skype.com/people/onv@onv.com.cn)

Website: [www.onvcom.com](http://www.onvcom.com)

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333,

Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou

