

Product Datasheet

44-port 10G Uplink Managed Industrial Ethernet Switch (ONV-IPS38448FM)



OVERVIEW

The ONV-IPS38448FM is a 10G uplink managed industrial Ethernet fiber switch independently developed by ONV. It has 12*10/100/1000Base-T adaptive RJ45 ports and 28*100/1000Base-X SFP fiber ports and 4*1/10G uplink SFP+ fiber ports. Each port can support wire-speed forwarding.

The ONV-IPS38448FM has L3 network management functions, supports IPV4/IPV6 management, dynamic routing and full line-speed forwarding, complete security protection mechanism, perfect ACL/QoS strategy, and rich VLAN functions for easy management and maintenance. Supports various industrial-grade redundant ring network protocols, each port can form a ring to support chain, star, double star, ring, tangent ring, intersecting ring, coupled ring, and the ring network self-heals within 20ms. Supports remote management and cooperates with ONV-NMS network management platform for cluster

management to achieve full-range blind spot network management. Complying with industrial product design and materials, it has excellent adaptability to industrial site environments (including mechanical stability, climate environment adaptability, electromagnetic environment adaptability, etc.). It is suitable for industrial scenarios such as intelligent transportation, rail transportation, power industry, mining, petroleum, shipping, metallurgy, and green energy construction to form an economical, efficient, stable, and reliable communication network.

FEATURE

■ Gigabit multi-fiber port access, uplink 1/10G SFP+ fiber port

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- ◇ Support Gigabit RJ45 port and 1/10G uplink SFP+ fiber port to meet the networking requirements of various scenarios.

■ Security

- ◇ Support port isolation and port broadcast storm suppression.
- ◇ Support IP+MAC+port+VLAN quadruple flexible combination binding function.
- ◇ Support 802.1X authentication to provide authentication functions for LAN computers, and control the authorization status of controlled ports according to the authentication results.

■ Strong business processing capability

- ◇ Support ERPS ring network and STP/RSTP/MSTP to eliminate layer 2 loops and realize link backup.
- ◇ Support IEEE802.1Q VLAN, Users can flexibly divide VLAN, Voice VLAN, and QinQ configuration according to their needs.
- ◇ Support static and dynamic aggregation to effectively increase link bandwidth, realize load balancing, link backup, and improve link reliability.
- ◇ Support QoS, port-based, 802.1P-based, and DSCP-based three priority modes and

four queue scheduling algorithms: Equ, SP, WRR, and SP+WRR.

- ◇ Support ACL to filter data packets by configuring matching rule processing operations and time permissions, and provide flexible security access control policies.
- ◇ Support IGMP V1/V2/V3 multicast protocol, IGMP Snooping meets multi-terminal high-definition video surveillance and video conference access requirements.

■ **Stable and reliable**

- ◇ CCC, CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR and Link.
- ◇ Self-developed power supply, redundant dual power supply provides long-term stable power output.
- ◇ Low power consumption, no fan, galvanized steel housing, an aluminum alloy heat sink combination, and excellent heat dissipation ensure the switch's stable operation.

■ **Easy O&M management**

- ◇ Support CPU monitoring, memory monitoring, Ping detection, and cable length detection.
- ◇ Support RMON, system log, and port traffic statistics to facilitate network optimization and transformation.
- ◇ Support HTTPS, SSLV3, SSHV1/V2, and other encryption methods, making management more secure.
- ◇ Supports LLDP, making it easier for the network management system to query and determine the communication status of the link.
- ◇ Support Web network management, CLI command line (Console, Telnet), SNMP (V1/V2/V3), and other diversified management and maintenance.

TECHNICAL SPECIFICATION

Model	ONV-IPS38448FM
Interface Characteristics	
Fixed Port	1*Console port (115200,N,8,1) 2*AC100-240V power input ports Power off alarm switch port (FAULT) 4*1/10G uplink SFP+ fiber ports (Data) 12*10/100/1000Base-T RJ45 ports (Data) 28*100/1000Base-X SFP fiber ports (Data) 2*DC12-48V power input ports (support anti-reverse protection)
Ethernet Port	Port 1-12 can support 10/100/1000Base-T(X) auto-sensing, full/ half duplex MDI/ MDI-X self-adaption
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meters) 100BASE-TX: Cat5 or later UTP(≤100 meters) 1000BASE-T: Cat5e or later UTP(≤100 meters)
Optical Fiber Port	1/10G SFP+ optical fiber port, default no include optical module (optional single-mode/ multi-mode, single fiber/ dual fiber optical module. LC)
Optical Fiber Port Expansion	Turbo overclocking 2.5G optical module expansion and ring network
Optical Cable/ Distance	Multi-mode: 850nm/ 0-550m, 850nm/ 0-300m(10G), Single-mode: 1310nm/ 0-40km, 1550nm/ 0-120km
Chip Parameter	
Network Management Type	L3
Network Protocol	IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3z 1000Base-X, IEEE 802.3ae 10GBase-LR/SR, IEEE 802.3x
Forwarding Mode	Store and Forward (Full Wire Speed)


Switching Capacity	176Gbps (non-blocking)
Forwarding Rate @64byte	119.04Mpps
CPU (Hz)	500M
DRAM	4G
FLASH	256M
MAC	32K
Buffer Memory	32M
Jumbo Frame	9.6K
LED Indicator	Power: PWR (Yellow), System: SYS (Yellow), Network: Link/Act (Yellow), Fiber port: L/A (Green)
Reset Switch	Yes, Press and hold the reset switch for 10s and release it to restore the factory settings
Power Supply	
Total PWR/ Input Voltage	60W/(AC100-240V)
Power Consumption	Standby<35W, Full Load<55W
Power Supply	Built-in power supply, AC 100~240V 50-60Hz, 0.65A
Power Input Port	Alarm switch port, 2*AC power input ports, 2*DC12-48V input ports Dual input power port design: AC power supply priority to support anti-reverse connection protection, and automatically switches to DC connection when power fails.
Physical Parameter	
Operation Temp/ Humidity	-40°C~+80°C, 5%~90% RH Non condensing
Storage Temp/ Humidity	-40°C~+85°C, 5%~95% RH Non condensing
Dimension (L*W*H)	440*298*44mm
Net /Gross Weight	4.0kg/4.8kg

Installation	Desktop, 1U/19" cabinet
Certification & Warranty	
Lightning Protection	<p>Protection level: IP40</p> <p>Lightning protection: 6KV 8/20us</p> <p>IEC61000-4-3(RS):10V/m (80~1000MHz)</p> <p>FCC Part 15/CISPR22(EN55022): Class B</p> <p>IEC61000-6-2(Common Industrial Standard)</p> <p>IEC61000-4-9(Pulsed magnet field): 1000A/m</p> <p>IEC61000-4-10(Damped oscillation): 30A/m, 1MHz</p> <p>IEC61000-4-12/18(Shockwave): CM 2.5kV, DM 1kV</p> <p>IEC61000-4-4(EFT): Power cable:±4kV, Data cable: ±2kV</p> <p>IEC61000-4-16(Common-mode transmission): 30V, 300V, 1s</p> <p>IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge</p> <p>IEC61000-4-6(Radio frequency transmission): 10V(150kHz~80MHz)</p> <p>IEC61000-4-8(Power frequency magnetic field):100A/m,1000A/m,1-3s</p> <p>IEC61000-4-5(Surge): Power cable: CM±4kV/DM±2kV, Data cable: ±4kV</p>
Mechanical Properties	IEC60068-2-6 (Anti Vibration), IEC60068-2-32 (Free Fall), IEC60068-2-27 (Anti Shock)
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15 Class B, RoHS
Warranty	5 years, lifelong maintenance.
Network Management Feature	
Interface	<p>Port temperature protection setting</p> <p>No connection port automatic sleep</p> <p>IEEE 802.3x flow control (Full duplex)</p> <p>Port green Ethernet Energy-saving setting</p> <p>Broadcast storm control based on port speed</p> <p>SFP+ optical port DDMI real-time digital diagnosis</p> <p>Limit the rate of packet traffic on incoming and outgoing ports, mini granularity is 64Kbps.</p>


L3 Feature	<p>Pingv6, Telnetv6, TFTPv6, DNSv6, ICMPv6</p> <p>IPV4/IPV6 VLANIF ports each support up to 128</p> <p>IPV4/IPV6 static route/ default route, max 128 entries</p> <p>IPV4 Equal Cost Routing, IPV4/IPV6 VRRP max 255 group</p> <p>NG protocol, max 1000 entries, ARP protocol, max 1000 entries</p> <p>L3 network management function, IPV4/IPV6 dual-stack management</p> <p>IPV4 dynamic routing, RIPv1/v2, OSPFv2, BGP4+, 4000 routing entries</p> <p>IPV6 dynamic routing OSPFv3, BGP+, RIPv6, IPV6 management, 1000 routing entries</p> <p>L3 routing and forwarding, support communication between different network segments and different VLAN</p>
VLAN	<p>Voice VLAN, QinQ configuration, IEEE 802.1q</p> <p>VLAN based on MAC, VLAN based on the protocol</p> <p>4K VLAN based on port, Port configuration of Access, Trunk, Hybrid.</p>
Port Aggregation	LACP dynamic aggregation, Static aggregation, Max 22 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d), RSTP (IEEE802.1w), MSTP (IEEE802.1s)
Industrial Ring Network Protocol	G.8032 (ERPS), Recovery time less than 20ms, 250 Ring at most, Max 250 devices per ring.
Multicast	MLD Snooping, Multicast VLAN, Fast log out, IGMP Snooping v1/v2/v3, Max 1024 multicast groups
Port Mirroring	Bidirectional data mirroring based on port
QoS	<p>Flow-based rate limiting, Flow-based redirection</p> <p>Queue scheduling algorithm (SP, WRR, SP+WRR)</p> <p>Flow-based packet filtering, 8*Output queues of each port</p> <p>802.1p/DSCP priority mapping, Diff-Serv QoS, Priority mark/ remark</p>
ACL	<p>ACL distribution based on port and VLAN</p> <p>L2-L4 packet filtering function, matching the first 80 bytes message, and provides ACL definitions based on source MAC address, destination MAC</p>

	address, source IP address, destination IP address, IP protocol type, TCP/UDP port, TCP/UDP port range, VLAN, etc.
Security	<p>IP source address protection</p> <p>ARP intrusion detection function</p> <p>ARP message rate limiting function</p> <p>Port broadcast message suppression</p> <p>AAA&RADIUS&TACACS+ certification</p> <p>SSL ensures data transmission security</p> <p>Anti-DoS attack, MAC address black hole</p> <p>Limit the number of MAC addresses learned</p> <p>Port isolation, Host data backup mechanism</p> <p>Quadruple binding function of IP+MAC+VLAN+port</p> <p>User hierarchical management and password protection</p> <p>SSH 2.0 provides a secure encrypted channel for user login</p> <p>IEEE802.1X authentication/ centralized MAC address authentication</p>
DHCP	DHCP Server, DHCP Client, DHCP Relay, DHCP Snooping
Management	<p>System work log, Dual system backup</p> <p>NTP clock, CPU real-time utilization status check</p> <p>One-click restore, Link layer discovery protocol LLDP</p> <p>FTP, TFTP, Xmodem, SFTP file upload and download management</p> <p>SNMP V1/V2/V3, Ping detection, Web network management (https)</p> <p>Console/AUX Modem/Telnet/SSH2.0 CLI command line configuration</p> <p>Cable length status detection, Mobile APP operation and maintenance</p> <p>ONV-NMS Network management platform cluster management (PC+cloud)</p>
System	<p>Web browser: Mozilla Firefox 2.5 or higher, Google Chrome V42 or higher, Cat5 and above Ethernet cable</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, Mac OS X) installed on each computer in the network Cat5 and above Ethernet cable</p>

DIMENSION



APPLICATION



ORDERING INFORMATION

Model	Description	Built-in Power Supply
ONV-IPS38448FM	L3 managed industrial Ethernet switch 12*10/100/1000M RJ45 ports and 28*100/1000M SFP fiber ports and 4*1/10G uplink SFP+ fiber ports. It has a built-in redundant dual power supply, supports 2AC+DC power terminal input, and 1U/19" cabinet installation.	2*60W

Note: The optical module is not included and needs to be purchased.

PACKING LIST

	Content	Qty	Unit
Packing List	44-port 10G uplink managed industrial Ethernet switch	1	SET
	AC Power Cable	1	PC
	RJ45-DB9 Adapter Cable	1	PC
	Mounting Kit	1	SET
	User Guide	1	PC
	Warranty Card and Certificate of Conformity	1	PC

OPTICAL MODULE

Product	Model	Description	Unit
1.25G Optica Module	2630-G	Industrial SFP optical module, 1.25G multi-mode dual fiber 850nm, transmission distance: 550m, LC interface. supports DDM function and hot plugging.	PC
	2632-G	Industrial SFP optical module, 1.25G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface. supports	PC

		DDM function and hot plugging.	
	2612-T-G	Industrial SFP optical module, 1.25G single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging.	PC
	2613-R-G	Industrial SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging.	PC
	2612-T-G-SC	Industrial SFP optical module, 1.25G single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, SC interface. supports DDM function and hot plugging.	PC
	2613-R-G-SC	Industrial SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, SC interface. supports DDM function and hot plugging.	PC
10G Optica Module	6630-G	Industrial SFP+ optical module, 10G multi-mode dual fiber 850nm, transmission distance: 300m, LC interface. supports DDM function and hot plugging.	PC
	7832-G	Industrial SFP+ optical module, 10G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging.	PC
	7832-33-G	Industrial SFP+ optical module, 10G single-mode single fiber TX1330nm/ RX1270nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging.	PC
	7832-27-G	Industrial SFP+ optical module, 10G single-mode single fiber TX1270nm/ RX13300nm, transmission distance: 20km, LC interface. supports DDM function and hot plugging.	PC

RELATED PRODUCT

Model	Description
ONV-IPS33018FM	L2+ managed industrial Ethernet fiber switch with 16*10/100/1000M RJ45 ports and 2*100/1000M uplink SFP fiber ports. It has a built-in redundant dual power supply, supports 2AC+DC power terminal input, and 1U/19" cabinet installation.
ONV-IPS38028FM	L3 managed industrial Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 4*1/10G uplink SFP+ fiber ports. It has a built-in redundant dual power supply, supports 2AC+DC power terminal input, and 1U/19" cabinet installation.
ONV-IPS38036FM	L3 managed industrial Ethernet fiber switch with 24*10/100/1000M RJ45 ports and 8*100/1000M SFP fiber ports and 4*1/10G uplink SFP+ fiber ports. It has a built-in redundant dual power supply, supports 2AC+DC power terminal input, and 1U/19" cabinet installation.
ONV-IPS38368FM	L3 managed industrial Ethernet fiber switch with 8*10/100/1000M RJ45 ports and 24*100/1000M SFP fiber ports and 4*1/10G uplink SFP+ fiber ports. It has a built-in redundant dual power supply, supports 2AC+DC power terminal input, and 1U/19" cabinet installation.
ONV-IPS38048FM	L3 managed industrial Ethernet fiber switch with 48*10/100/1000M RJ45 ports and 4*1/10G uplink SFP+ fiber ports. It has a built-in redundant dual power supply, supports 2AC+DC power terminal input, and 1U/19" cabinet installation.

CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn



Skype: onv@onv.com.cn

WeChat ID: ONV-PoE-IoT

Website: www.onvcom.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333,

Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou

