

Product Datasheet

6-port 10/100M Non-standard PoE Switch

(ONV-H2064P)



OVERVIEW

The ONV-H2064P is a 10/100M non-standard PoE switch independently developed by ONV. It has 6*10/100M RJ45 ports. Port 1-4 can support 24V non-standard PoE power supply and the single-port PoE power up to 24W. As a non-standard PoE power supply device, it must be connected to the corresponding non-standard electrical equipment (such as wireless bridge), or the corresponding non-standard PoE splitter to convert, and then achieve the PoE power supply. It can supply power to various adaptable terminals through network cables to meet the demand for a high-density PoE power supply network environment. It is suitable for hotels, campuses, factory dormitories, and small and medium-sized enterprises to establish cost-effective networks. Unmanaged mode, plug and play, no configuration, easy to use.

FEATURE

■ 10/100M access

- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE 802.3x and half-duplex based on Backpressure.
- ◇ Provides 6*10/100M RJ45 ports, which is more convenient for users to flexibly set up to meet the network requirements of various scenarios.

■ Smart PoE power supply

- ◇ 4*10/100Base-TX RJ45 ports support 24V PoE power supply, meeting the power supply needs of security monitoring, wireless coverage, and other scenarios.
- ◇ Quickly implement PoE network cable power supply through the switch to directly connect non-standard electrical equipment or the switch and non-standard PoE splitter cable.

■ Stable and reliable


- ◇ CCC, CE, FCC, RoHS.
- ◇ Plug and play, no configuration, simple and convenient.
- ◇ The user-friendly panel can show the device status through the LED indicator of PWR and L/A.
- ◇ Self-developed power supply, high redundancy design, providing a long-term and stable PoE power output.
- ◇ Low power consumption, galvanized steel housing, and excellent heat dissipation to ensure the stable operation of the switch.

TECHNICAL SPECIFICATION


Model	ONV-H2064P
Interface Characteristics	
Fixed Port	2*10/100Base-TX uplink RJ45 Ports (Data) 4*10/100Base-TX 24V PoE ports (Data /Power)
Ethernet Port	Port 1- 6 can support 10/100Base-TX auto-sensing, full/ half duplex MDI/ MDI-X self-adaption
Twisted Pair Transmission	10BASE-TX: Cat5 or later UTP (≤100 meters) 100BASE-TX: Cat5 or later UTP (≤100 meters)
Chip Parameter	
Network Protocol	IEEE 802.3 10BASE-T, IEEE 802.3i 10Base-T, IEEE 802.3u 100Base-TX, IEEE802.3x

Forwarding Mode	Store and Forward (Full Wire Speed)
Switching Capacity	1.2Gbps (non-blocking)
Forwarding Rate@64byte	0.89Mpps
MAC	1K
Buffer Memory	768K
Jumbo Frame	1536byte
LED Indicator	Power: PWR (Green), Network: L/A (Green)
PoE& Power Supply	
PoE Port	Port 1-4 can support 24V PoE power
Power Supply Pin	4/5(+), 7/8 (-)
Max Single Port/ Average Power	24W/15W
Total PWR/ Input Voltage	60W /(AC100-240V)
Power Consumption	Standby<5W, Full load<60W
Power Supply	Built-in power supply, AC100~240V, 50-60Hz, 1.0A
Physical Parameter	
Operation Temp/ Humidity	-20~+55°C, 5%~90% RH Non condensing
Storage Temp/ Humidity	-40~+75°C, 5%~95% RH Non condensing
Dimension (L*W*H)	142.5*115*40mm
Net /Gross Weight	0.55kg/ 0.8kg
Installation	Desktop, Wall mount
Certification & Warranty	
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30
Certification	CCC, CE mark, commercial, CE/LVD EN62368-1, FCC Part 15, RoHS
Warranty	1 year, lifelong maintenance.

DIMENSION



APPLICATION



ORDERING INFORMATION

Model	Description	Built-in Power Supply
ONV-H2064P	Unmanaged PoE switch with 4*10/100M RJ45 ports and 2*10/100M uplink RJ45 ports. Port 1-4 can support DC24V PoE output. Built-in power supply.	60W

Note: The mounting ears are not included and need to be purchased.

PACKING LIST

	Content	Qty	Unit
Packing List	6-port 10/100M non-standard PoE switch	1	Set
	AC Power Cable	1	PC
	User Guide	1	PC
	Warranty Card and Certificate of Conformity	1	PC

CONTACT US



Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

Email: onv@onv.com.cn

Skype: onv@onv.com.cn

WeChat ID: ONV-PoE-IoT

Website: www.onvcom.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333, Zhongkai 6th

Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou

