Product Datasheet

19-port Gigabit Easy Managed PoE Switch

(ONV-H53016PFMS)



OVERVIEW

The ONV-H53016PFMS is a Gigabit Easy managed PoE switch independently developed by ONV. It features 16*10/100/1000Base-T adaptive RJ45 ports and 2*10/100/1000Base-T RJ45 ports and 1*100/1000M SFP fiber port. Ports 1-16 support the IEEE 802.3af/at PoE standard with single-port PoE power of 30W. As PoE power-sourcing equipment, the switch automatically detects and identifies compliant powered devices and supplies power to them via Ethernet cables. It can provide power to various PoE-enabled terminal devices—such as wireless access points, IP cameras, VoIP phones, and video intercom systems—making it an ideal solution for network environments that require high-density PoE deployment. It is suitable for hotels, campuses, factory dormitories, and small- to medium-sized businesses looking to build cost-effective, efficient networks.

The ONV-H53016PFMS supports web management, the ONV-NMS cloud management platform, and mobile app management. It enables features such as security network

topology management, VLAN configuration, port management, PoE management, and remote operation and maintenance. This switch offers high reliability, ease of installation and maintenance, high-speed switching capabilities, and multiple access ports, making it suitable for connecting devices in local area networks (LANs) of various scales.

FEATURE

Gigabit access, uplink RJ45/SFP fiber port

◇ Support non-blocking wire-speed forwarding.

◇ Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.

◇ Supports Gigabit RJ45 port and SFP fiber port combination, which enables users to build networking to meet the needs of various scenarios flexibly.

Smart PoE power supply

◇ Supports remote PoE management, enabling remote on/off of each PoE port, viewing of port power status, and PoE port fault query.

◇ Complies with the IEEE 802.3 af/at PoE standard, automatically identifies PoE devices for power supply, and does not damage non-PoE devices.

◇ 16*10/100/1000Base-T RJ45 ports support PoE power to meet the needs of security monitoring, teleconferencing systems, wireless coverage, and other scenarios.

Minimalist application

◇ Support real-time fault alarms and fault location.

◇ Support remote upgrades, remote reboots, and factory resets.

◇ Cloud platform and mobile APP operation and maintenance management: visualized PoE power supply control, network topology management, and VLAN segmentation.

◇ It abandons complex network management configurations, retaining only practical network management functions, enabling rapid network deployment and centralized operation and maintenance through the operation and maintenance platform.

Stable and reliable

- ◇ CE, FCC, RoHS.
- ◇ The user-friendly panel can show the device status through the LED indicators for PWR, SYS, Link, and PoE.
- ◇ Low power consumption, galvanized steel housing, and excellent heat dissipation ensure the stable operation of the switch.


TECHNICAL SPECIFICATION

Model	ONV-H53016PFMS
Interface Characteristics	
Fixed Port	2*10/100/1000Base-T RJ45 ports (Data) 1*100/1000Base-X uplink SFP fiber port (Data) 16*10/100/1000Base-T PoE ports (Power/ Data)
Ethernet Port	Ports 1-16 support 10/100/1000Base-T(X) auto-sensing, full/ half duplex MDI/ MDI-X self-adaptation
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP (≤100 meters) 100BASE-TX: Cat5 or later UTP (≤100 meters) 1000BASE-T: Cat5e or later UTP (≤100 meters)
Optical Fiber Port	Gigabit SFP fiber port; optical module not included (optional single-mode/ multi-mode, single-fiber/dual-fiber modules, LC)
Optical Cable/ Distance	Multi-mode: 850nm/ 0-550m, Single-mode: 1310nm/ 0-40km, 1550nm/ 0-120km.
Chip Parameter	
Network Management Type	L2 (Web management, platform management)
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x
Forwarding Mode	Store and forward (Full wire speed)
Switching Capacity	38Gbps (non-blocking)

Forwarding Rate@64byte	28.27Mpps
MAC	4K
Buffer Memory	2M
Jumbo Frame	9.2K
LED Indicator	Power/System: SYS (Green), Fiber: L/A (Green), Network: Link (Green), POE: PoE (Red)
Reset Switch	Slide the DIP switch from left to right, hold for 1–3 seconds, then slide it back from right to left; this performs a reset. Positioned to the left: Web (management mode); positioned to the right: unmanaged mode.
PoE& Power Supply	
PoE Port	Port 1-16
PoE Management	Port PoE output on/off, Port PoE operating status display
Power Supply Pin	1/2(+) 3/6(-)
Max Power Per Port	30W, IEEE 802.3 af/at
Total PWR/ Input Voltage	250W/ (AC100-240V)
Power Consumption	Standby<15W, full load<250W
Power Supply	Built-in power supply, AC100~240V 50-60Hz, 4.1A
Physical Parameter	
Operation Temp/ Humidity	-20°C~+55°C, 5%~90% RH non-condensing
Storage Temp/ Humidity	-40°C~+80°C, 5%~95% RH non-condensing
Dimension (L*W*H)	350*215*44mm
Net /Gross Weight	<1.85kg/ <2.4kg
Installation	Desktop, wall mount
Certification& Warranty	
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30
Certification	CE, FCC, RoHS
Warranty	1 year, lifelong maintenance
Network Management Feature	

System Management	IP settings, Account management, Port traffic settings, System information display
VLAN	MTU VLAN
Security	Broadcast storm control, Port isolation, Port speed limit
Management	ONV-NMS Platform management(Cloud Platform), One-key recovery Mobile APP operation and maintenance management, Web Management
System	Web browser: Mozilla Firefox 2.5 or higher, Google Chrome 42 or higher, Cat5 and above Ethernet cable TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, Mac OS X) installed on each computer in the network Cat5 and above Ethernet cable

DIMENSION



APPLICATION

ORDERING INFORMATION

Model	Description	Built-in Power Supply
ONV-H53016PFMS	Easy managed PoE switch with 18*10/100/1000M RJ45 ports and 1*100/1000M uplink SFP fiber port. Ports 1-16 support the IEEE 802.3 af/at PoE standard. It has a built-in power supply and supports desktop and wall-mount.	250W
Note: The optical module is not included and needs to be purchased.		

PACKING LIST

	Content	Qty	Unit
Packing List	19-port Gigabit Easy managed PoE switch	1	PC
	AC Power Cable	1	PC
	User Guide	1	PC
	Warranty Card and Certificate of Conformity	1	PC

OPTICAL MODULE

Product	Model	Description	Unit
1.25G Optical Module	2630	SFP optical module, 1.25G multi-mode dual fiber 850nm, transmission distance: 550m, LC interface. Supports DDM function and hot-plugging.	PC
	2632	SFP optical module, 1.25G single-mode dual fiber 1310nm, transmission distance: 20km, LC interface. Supports DDM function and hot-plugging.	PC
	2612-T	SFP optical module, 1.25G single-mode single fiber TX1310nm/ RX1550nm, transmission distance: 20km, LC interface. Supports DDM function and hot-plugging.	PC
	2613-R	SFP optical module, 1.25G single-mode single fiber TX1550nm/ RX1310nm, transmission distance: 20km, LC interface. Supports DDM function and hot-plugging.	PC

CONTACT US

Optical Network Video Technologies (Shenzhen) Co., Ltd.

Tel: 0086-755-33376606

Fax: 0086-755-33376608

WeChat: ONV-PoE-IoT

Email: onv@onv.com.cn

Website: www.onvcom.com, www.onvswitch.com

Headquarter Address: Room 1003, Block D, Terra Building, Futian District, Shenzhen

Factory Address: Building B3, Galaxy Artificial Intelligence Industrial Park, No. 333, Zhongkai 6th Road, Chenjiang Street, Zhongkai High-tech Zone, Huizhou

